

PN1	1	2	3	4	5	6	7	8	9	10	11	12	13	14
ESD	SE01	SE02	SE03	SE04	SE05	SE06	SE07	SE08	SE09	SE10	SE11	SE12	SE13	SE14
COM1	S0	S1	S2	S3	S4	S5	S6	S7	S8	S9	S10	S11	S12	S13
COM2	S5	S6	S7	S8	S9	S10	S11	S12	S13	S14	S15	S16	S17	S18
COM3	S4	S5	S6	S7	S8	S9	S10	S11	S12	S13	S14	S15	S16	S17
COM4	S3	S4	S5	S6	S7	S8	S9	S10	S11	S12	S13	S14	S15	S16

Pin No.	Symbol
1	CS
2	RD
3	WR
4	DATA
5	VSS
6	VDD

Specification

1. Display mode: FSTN/POSITIVE/REFLECTIVE
2. Driving condition: 1/4Duty, 1/3 Bias Vop= 4.5V Vdd=5.0V
3. Operating temp: -0°C to 50°C , Storage temp: -10°C to 60°C
4. IC NO. : HT1621 5. Viewing angle : 6 O'clock
6. BACKLIGHT: WITHOUT BACKLIGHT
7. Unspecified tolerance : ± 0.30mm
8. LCD NO. : GPS0602C1
9. Remark: ROHS


Count drawing & Spec: revision record during discussion with customer

Rev	Revision content description	Date
#00	FIRST ISSUE	2016.09.30
#01	MODIFY THE THICK OF PRODUCTION	2016.10.12
#02	MODIFY PCB AND GLASS SIZES	2017.02.21
#03	MODIFY ICON	2017.08.28
#04	MODIFY ICON	2017.09.28

JASONIC TECHNOLOGY LIMITED

Mod Name		GBD006A1	
UNIT	SIZE	DESIGNER	CHECK
mm	A4		
APPROVER		APPROVER	

1. (.) : REFERENCE DIMENSION.
2. □ : IMPORTANT DIMENSION.



SCALE	SHEET
NTS	1/2
FILE NAME	Count Dwg.