



NOTE:

1. GENERAL TOLERANCE: $\pm 0.2\text{mm}$
2. THE PART OF *ARE THE KEY DIMENSION TO CONTROL

1. Display mode: **FSTN/POSITIVE/REFLECTIVE**, Viewing angle: 6 O'clock
2. Driving condition: 1/4Duty, 1/3Bias, Vop: 3.0V
3. Operating temp: -20°C~70°C, Storage temp: -30°C~80°C
4. Back light: Non, HEAT SEAL
5. Back light color chromaticity: X:0.27~0.31; Y:0.27~0.31;
6. Uniformity of the lightguide more than 70%
7. Unspecified tolerance: $\pm 0.20\text{mm}$
8. Remark: ROHS

Count drawing & Spec.revision record during discussion with customer	Rec: #00	Revision content description: FIRST ISSUE	Date: 2014.09.24
--	----------	---	------------------

JASONIC TECHNOLOGY LIMITED		Mod.Name	JOD207A5	UNIT	mm
		DESIGNER	CHECK	APPROVER	FILE NAME
SCALE	SHEE	NTS	1/1	Count Dwg.	

SEG	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
COM1						1F	1A	2F	2A	3F	3A	4F	4A	5F	5A
COM2		COM2				1G	1B	2G	2B	3G	3B	4G	4B	5G	5B
COM3			COM3			1E	1C	2E	2C	3E	3C	4E	4C	5E	5C
COM4				COM4	T4	1D		2D		3D	P	4D	S	5D	

(1-3) SCALE 1:1
(4-5) SCALE 2:1