



**Feature**

1. 240x64 dots includes cursor
2. Built-in controller (RA6963 or equivalent)
3. +5V power supply(Also available for +3V)
4. 1/64duty cycle
5. LED can be driven by pin2,pin3,or A and K

**Mechanical Data**

Item	Value	Unit
Outline	180.0 x 65.0	mm
Viewing Area	133.0 x 39.0	mm
Active Area	127.16 x 33.88	mm
Dot Size	0.49 x 0.49	mm
Dot Pitch	0.53 x 0.53	mm

**Terminal Function**

Pin No.	Symbol	Function
1	FG	Frame ground
2	Vss	GND
3	V <sub>DD</sub>	Supply voltage for logic
4	V <sub>0</sub>	Contrast Adjustment
5	/WR	Data write s
6	/RD	Data read
7	/CE	H-L Enable signal
8	C/D	Command/data read/write
9	V <sub>ee</sub>	Negative Voltage output
10	/RST	Reset signal
11-18	DB0-DB7	H/L Data bus line
19	FS	FS="H",6*8character font FS="L",8*8character font
20	NC/ V <sub>ee</sub>	No connection/ Negative Voltage output

**Electrical Characteristics**

Item	Symbol	Min	Typ	Max
Operating Voltage(V)	V <sub>DD</sub>	4.7	5.0	5.3
Supply Voltage For LCD	V <sub>DD</sub> - V <sub>0</sub>	—	12.5	—
Input High Voltage(V)	V <sub>IH</sub>	0.7	—	V <sub>DD</sub>
Input Low Voltage(V)	V <sub>IL</sub>	V <sub>SS</sub>	—	0.6
Operating Current(mA)	I <sub>DD</sub>	—	45	50

**Backlight Characteristics**

Item	Symbol	Min	Typ	Max	Unit
Forward Voltage	V <sub>f</sub> (edge)	3.4	3.5	3.6	V
Forward Current	I <sub>f</sub> (edge)	48	64	80	mA
Forward Voltage	V <sub>f</sub> (array)	-	4.2	4.4	V
Forward Current	I <sub>f</sub> (array)	-	660	900	mA

**Absolute Maximum**

Item	Symbo	Min	Max
Operating Voltage(V)	V <sub>dd</sub>	-0.3	5.5
Operating Temperature(°C)	Top	-20	+70
Storage Temperature (°C)	T <sub>st</sub>	-30	+80